

## **Dimming Compatibility**

ID E2010024V0

**Product Family:** 

Sku Tested: PD-50117

**Related Models** 

Test Voltage: 120-277V

**Control Type:** 

Test Notes: Refer to dimmer manufacturer's dimmer load rating for min and max fixture quantities per dimmer.

Manufacturer	Product	Model Number	Test Voltage (V)	Measured Dimming Range Low End	Comments				
Adaptive Phase Dimmers									
Control4	Adaptive	C4-APD120	120	0.4%					
Legrand	Adorne Touch (ELV)	ADTH700RMTUM1	120	1.0%					
Legrand	Adorne Touch (TRIAC)	ADTH700RMTUM1	120	0.3%	Not Recommended				
Legrand	Radiant	RH703PTUW	120	15.0%	Noise at 1 meter away				
Legrand	Adorne (ELV)	ADTP703TUW4	120	11.0%					
Legrand	Adorne (TRIAC)	ADTP703TUW4	120	10.0%	Not Recommended				
Cooper	AL Series	AAL06	120	1.0%	Noise at 1 meter away				
Control4	Adaptive	C4-APD277	277	N/A	Not Recommended				
Reverse Phase Dimmers (ELV)									
Lutron	Nova T	NTELV-600	120	7.0%					
Lutron	Diva	DVELV-300P	120	4.0%					
Lutron	Maestro	MAELV-600	120	0.9%					
Lutron	Skylark	SELV-300P	120	N/A	Dimmer not responsive				
Leviton	Illumatech	IPE04-1LZ	120	5.0%					
Lutron	Maestro	RRD-6NA	120	0.9%					
Leviton	SureSlide	6615-P0W	120	14.0%					
Leviton	Decora	DSE06-10Z	120	2.0%					
Lutron	Caseta	PD-5NE	120	5.0%					
Lutron	Homeworks	HRD-5NE	120	3.0%					
Lutron	Homeworks	HQRD-6NA	120	0.9%					
Leviton	Renoir II	AWSMT-EBW	120	0.3%					
Lutron	Grafik-Eye	GRX-3103-A-G	120	0.5%					
Leviton	Renoir II	AWSMT-EBW	277	N/A	Not Recommended				
Lutron	Grafik-Eye	GRX-3103-A-G	277	N/A	Not Recommended				
Forward Phase Dimmers (TRIAC)									
Lutron	Maestro	MACL-153M-WH	120	8.0%	Noise at 1 meter away				
Lutron	Diva	DVCL-153P	120	0.5%	Noise at 1 meter away				
Legrand	Adorne Paddle	ADPD453LW2	120	15.0%	Noise at 1 meter away				
Lutron	Ariadni	AYCL-153PH	120	2.0%					

Perceived light level percentage is the square root of the measured light level percentage, per IESNA Lighting Handbook. This report reflects Modern Forms's test results of a single fixture in single-pole wiring configuration for reference purposes; actual results may vary based on field conditions. Dimmer manufacturers may modify their product at any time, without notice to Modern Forms, and therefore Modern Forms cannot ensure future compatibility. For any questions on this report, please contact Modern Forms Customer Service at 1-866-810-6615 or customerservice@modernforms.com.

## MODERN FORMS

Forward Phase Dimmers (TRIAC) Cont.								
Lutron	Skylark	SCL-153P-WH	120	0.5%				
Lutron	Maestro	MA-600-WH	120	N/A	Dimmer not responsive			
Leviton	SureSlide	6674-POW	120	3.0%				
Lutron	Caseta	PD-6WCL	120	22.0%	Flicker below 22%; Noise at 1 meter away			
Legrand	Harmony	HCL453PW	120	25.0%	Flicker below 25%; Noise at 1 meter away			
Legrand	Radiant	RHCL453PW	120	5.0%	Noise at 1 meter away			

Perceived light level percentage is the square root of the measured light level percentage, per IESNA Lighting Handbook. This report reflects Modern Forms's test results of a single fixture in single-pole wiring configuration for reference purposes; actual results may vary based on field conditions. Dimmer manufacturers may modify their product at any time, without notice to Modern Forms, and therefore Modern Forms cannot ensure future compatibility. For any questions on this report, please contact Modern Forms Customer Service at 1-866-810-6615 or customerservice@modernforms.com.