

Product Family: Stella, Loft
Sku Tested: WS-13217
Related Model Numbers: WS-3618

Test Voltage: 120V
Control Type: ELV
Test Notes: Refer to dimmer manufacturer's dimmer load rating for min and max fixture quantities per dimmer.

Manufacturer	Product	Model Number	Test Voltage (V)	Measured Dimming Range	Comments
				Low End	
Adaptive Phase Dimmers					
Control4	Adaptive	C4-APD120	120	4.0%	
Legrand	Adorne Touch (ELV)	ADTH700RMTUM1	120	4.0%	
Legrand	Adorne Touch (TRIAC)	ADTH700RMTUM1	120	3.0%	Not Recommended
Legrand	Radiant	RH703PTUW	120	9.0%	
Legrand	Adorne (ELV)	ADTP703TUW4	120	4.0%	
Legrand	Adorne (TRIAC)	ADTP703TUW4	120	4.0%	Not Recommended
Cooper	AL Series	AAL06	120	3.0%	
Reverse Phase Dimmers (ELV)					
Lutron	Nova T	NTELV-600	120	4.0%	
Lutron	Diva	DVELV-300P	120	4.0%	
Lutron	Maestro	MAELV-600	120	4.0%	
Lutron	Skylark	SELV-300P	120	4.0%	
Leviton	Illumatech	IPE04-1LZ	120	10.0%	
Lutron	Maestro	RRD-6NA	120	3.0%	
Leviton	SureSlide	6615-POW	120	6.0%	
Leviton	Decora	DSE06-10Z	120	4.0%	
Lutron	Caseta	PD-5NE	120	3.0%	
Lutron	Homeworks	HRD-5NE	120	N/A	Flashing at high dimming level
Leviton	Renoir II	AWSMT-EBW	120	5.0%	
Lutron	Grafik-Eye	GRX-3103-A-G	120	4.0%	
Forward Phase Dimmers (TRIAC)					
Lutron	Maestro	MAELV-153M-WH	120	3.0%	Not Recommended
Lutron	Diva	DVCL-153PD	120	3.0%	Not Recommended
Legrand	Adorne Paddle	ADPD453LW2	120	6.0%	Not Recommended
Lutron	Ariadni	AYCL-153PH	120	3.0%	Not Recommended
Lutron	Skylark	SCL-153P-WH	120	3.0%	Not Recommended
Lutron	Maestro	MA-600-WH	120	N/A	Not Recommended
Leviton	SureSlide	6674-POW	120	3.0%	Not Recommended

Perceived light level percentage is the square root of the measured light level percentage, per IESNA Lighting Handbook. This report reflects WAC's test results of a single fixture in single-pole wiring configuration for reference purposes; actual results may vary based on field conditions. Dimmer manufacturers may modify their product at any time, without notice to WAC Lighting, and therefore WAC Lighting cannot ensure future compatibility. For any questions on this report, please contact WAC Lighting Customer Service at 1-800-526-2588 or sales@wacighting.com.

WAC LIGHTING
Responsible Lighting®

Forward Phase Dimmers (TRIAC) Cont.					
Lutron	Caseta	PD-6WCL	120	3.0%	Not Recommended
Legrand	Harmony	HCL453PW	120	3.0%	Not Recommended
Legrand	Radiant	RHCL453PW	120	4.0%	Not Recommended

Perceived light level percentage is the square root of the measured light level percentage, per IESNA Lighting Handbook. This report reflects WAC's test results of a single fixture in single-pole wiring configuration for reference purposes; actual results may vary based on field conditions. Dimmer manufacturers may modify their product at any time, without notice to WAC Lighting, and therefore WAC Lighting cannot ensure future compatibility. For any questions on this report, please contact WAC Lighting Customer Service at 1-800-526-2588 or sales@waclighting.com.

Product Family: Loft
Sku Tested: WS-3624-BN
Related Model Numbers: N/A

Test Voltage: 120V
Control Type: ELV
Test Notes: Refer to dimmer manufacturer's dimmer load rating for min and max fixture quantities per dimmer.

Manufacturer	Product	Model Number	Test Voltage (V)	Measured Dimming Range	Comments
				Low End	
Adaptive Phase Dimmers					
Control4	Adaptive	C4-APD120	120	3.0%	Flicker below 3%
Legrand	Adorne Touch (ELV)	ADTH700RMTUM1	120	3.0%	
Legrand	Adorne Touch (TRIAC)	ADTH700RMTUM1	120	3.0%	Not Recommended
Legrand	Radiant	RH703PTUW	120	9.0%	
Legrand	Adorne (ELV)	ADTP703TUW4	120	4.0%	
Legrand	Adorne (TRIAC)	ADTP703TUW4	120	3.0%	Not Recommended
Cooper	AL Series	AAL06	120	N/A	
Reverse Phase Dimmers (ELV)					
Lutron	Nova T	NTELV-600	120	4.0%	
Lutron	Diva	DVELV-300P	120	6.0%	
Lutron	Maestro	MAELV-600	120	6.0%	
Lutron	Skylark	SELV-300P	120	5.0%	
Leviton	Illumatech	IPE04-1LZ	120	10.0%	
Lutron	Maestro	RRD-6NA	120	4.0%	
Leviton	SureSlide	6615-POW	120	6.0%	
Leviton	Decora	DSE06-10Z	120	4.0%	
Lutron	Caseta	PD-5NE	120	3.0%	
Lutron	Homeworks	HRD-5NE	120	N/A	Flashing at high dimming level
Leviton	Renoir II	AWSMT-EBW	120	3.0%	
Lutron	Grafik-Eye	GRX-3103-A-G	120	3.0%	
Forward Phase Dimmers (TRIAC)					
Lutron	Maestro	MACL-153M-WH	120	4.0%	Not Recommended
Lutron	Diva	DVCL-153PD	120	3.0%	Not Recommended
Legrand	Adorne Paddle	ADPD453LW2	120	6.0%	Not Recommended
Lutron	Ariadni	AYCL- 153PH	120	5.0%	Not Recommended
Lutron	Skylark	SCL-153P-WH	120	3.0%	Not Recommended
Lutron	Maestro	MA-600-WH	120	N/A	Not Recommended
Leviton	SureSlide	6674-POW	120	5.0%	Not Recommended

Perceived light level percentage is the square root of the measured light level percentage, per IESNA Lighting Handbook. This report reflects WAC's test results of a single fixture in single-pole wiring configuration for reference purposes; actual results may vary based on field conditions. Dimmer manufacturers may modify their product at any time, without notice to WAC Lighting, and therefore WAC Lighting cannot ensure future compatibility. For any questions on this report, please contact WAC Lighting Customer Service at 1-800-526-2588 or sales@wacighting.com.

WAC LIGHTING
Responsible Lighting®

Forward Phase Dimmers (TRIAC) Cont.					
Lutron	Caseta	PD-6WCL	120	3.0%	Not Recommended
Legrand	Harmony	HCL453PW	120	3.0%	Not Recommended
Legrand	Radiant	RHCL453PW	120	3.0%	Not Recommended

Perceived light level percentage is the square root of the measured light level percentage, per IESNA Lighting Handbook. This report reflects WAC's test results of a single fixture in single-pole wiring configuration for reference purposes; actual results may vary based on field conditions. Dimmer manufacturers may modify their product at any time, without notice to WAC Lighting, and therefore WAC Lighting cannot ensure future compatibility. For any questions on this report, please contact WAC Lighting Customer Service at 1-800-526-2588 or sales@waclighting.com.

MODERN FORMS

Dimming Compatibility

ID E1812043V0

Product Family: Loft

Sku Tested: WS-3632

Related Models N/A

Test Voltage: 120V

Control Type:

Test Notes: Refer to dimmer manufacturer's dimmer load rating for min and max fixture quantities per dimmer.

Manufacturer	Product	Model Number	Test Voltage (V)	Measured Dimming Range	Comments
				Low End	
Adaptive Phase Dimmers					
Control4	Adaptive	C4-APD120	120	4.0%	
Legrand	Adorne Touch (ELV)	ADTH700RMTUM1	120	50.0%	Flicker at high dimming level
Legrand	Adorne Touch (TRIAC)	ADTH700RMTUM1	120	53.0%	Not Recommended
Legrand	Radiant	RH703PTUW	120	7.0%	
Legrand	Adorne (ELV)	ADTP703TUW4	120	4.0%	Turn on time >0.5s at the lowest dimming level
Legrand	Adorne (TRIAC)	ADTP703TUW4	120	3.0%	Not Recommended
Cooper	AL Series	AAL06	120	N/A	Flashing at the highest dimming level
Reverse Phase Dimmers (ELV)					
Lutron	Nova T	NTELV-600	120	5.0%	
Lutron	Diva	DVELV-300P	120	4.0%	
Lutron	Maestro	MAELV-600	120	4.0%	
Lutron	Skylark	SELV-300P	120	5.0%	
Leviton	Illumatech	IPE04-1LZ	120	9.0%	
Lutron	Maestro	RRD-6NA	120	4.0%	
Leviton	SureSlide	6615-POW	120	5.0%	
Leviton	Decora	DSE06-10Z	120	4.0%	
Lutron	Caseta	PD-5NE	120	4.0%	
Lutron	Homeworks	HRD-5NE	120	N/A	Flashing at high dimming level
Lutron	Homeworks	HQRD-6NA	120	4.0%	
Leviton	Renoir II	AWSMT-EBW	120	N/A	Flicker at the highest dimming level
Lutron	Grafik-Eye	GRX-3103-A-G	120	N/A	Flashing at the highest dimming level
Forward Phase Dimmers (TRIAC)					
Lutron	Maestro	MACL-153M-WH	120	43.0%	Not Recommended
Lutron	Diva	DVCL-153P	120	39.0%	Not Recommended
Legrand	Adorne Paddle	ADPD453LW2	120	35.0%	Not Recommended
Lutron	Ariadni	AYCL-153PH	120	20.0%	Not Recommended
Lutron	Skylark	SCL-153P-WH	120	42.0%	Not Recommended
Lutron	Maestro	MA-600-WH	120	N/A	Not Recommended
Leviton	SureSlide	6674-POW	120	13.0%	Not Recommended
Lutron	Caseta	PD-6WCL	120	35.0%	Not Recommended
Legrand	Harmony	HCL453PW	120	50.0%	Not Recommended
Legrand	Radiant	RHCL453PW	120	20.0%	Not Recommended

Perceived light level percentage is the square root of the measured light level percentage, per IESNA Lighting Handbook. This report reflects Modern Forms's test results of a single fixture in single-pole wiring configuration for reference purposes; actual results may vary based on field conditions. Dimmer manufacturers may modify their product at any time, without notice to Modern Forms, and therefore Modern Forms cannot ensure future compatibility. For any questions on this report, please contact Modern Forms Customer Service at 1-866-810-6615 or customerservice@modernforms.com.