

Dimming Compatibility

ID E1911069V0

Product Family: QUARRY Sku Tested: WS-60018

Related Models

Test Voltage: 120V Control Type: ELV

Test Notes: Refer to dimmer manufacturer's dimmer load rating for min and max fixture quantities per dimmer.

Manufacturer	Product	Model Number	Test Voltage (V)	Measured Dimming Range	Comments					
				Low End						
	Adaptive Phase Dimmers									
Control4	Adaptive	C4-APD120	120	8.0%						
Legrand	Adorne Touch (ELV)	ADTH700RMTUM1	120	18.0%	Flicker below 18%					
Legrand	Adorne Touch (TRIAC)	ADTH700RMTUM1	120	63.0%	Not Recommended					
Legrand	Radiant	RH703PTUW	120	15.0%	Flicker below 15%					
Legrand	Adorne (ELV)	ADTP703TUW4	120	7.0%						
Legrand	Adorne (TRIAC)	ADTP703TUW4	120	8.0%	Not Recommended					
Cooper	AL Series	AAL06	120	76.0%	Flicker at high dimming level					
	Reverse Phase Dimmers (ELV)									
Lutron	Nova T	NTELV-600	120	8.0%						
Lutron	Diva	DVELV-300P	120	8.0%						
Lutron	Maestro	MAELV-600	120	8.0%						
Lutron	Skylark	SELV-300P	120	8.0%						
Leviton	Illumatech	IPE04-1LZ	120	8.0%						
Lutron	Maestro	RRD-6NA	120	7.0%						
Leviton	SureSlide	6615-P0W	120	7.0%						
Leviton	Decora	DSE06-10Z	120	8.0%						
Lutron	Caseta	PD-5NE	120	7.0%						
Lutron	Homeworks	HRD-5NE	120	N/A	Flashing at high dimming level					
Lutron	Homeworks	HQRD-6NA	120	7.0%						
Leviton	Renoir II	AWSMT-EBW	120	7.0%						
Lutron	Grafik-Eye	GRX-3103-A-G	120	8.0%						
Forward Phase Dimmers (TRIAC)										
Lutron	Maestro	MACL-153M-WH	120	7.0%	Not Recommended					
Lutron	Diva	DVCL-153P	120	7.0%	Not Recommended					
Legrand	Adorne Paddle	ADPD453LW2	120	9.0%	Not Recommended					
Lutron	Ariadni	AYCL-153PH	120	36.0%	Not Recommended					
Lutron	Skylark	SCL-153P-WH	120	39.0%	Not Recommended					
Lutron	Maestro	MA-600-WH	120	N/A	Not Recommended					
Leviton	SureSlide	6674-POW	120	43.0%	Not Recommended					
Lutron	Caseta	PD-6WCL	120	N/A	Not Recommended					
Legrand	Harmony	HCL453PW	120	N/A	Not Recommended					
Legrand	Radiant	RHCL453PW	120	N/A	Not Recommended					

Perceived light level percentage is the square root of the measured light level percentage, per IESNA Lighting Handbook. This report reflects Modern Forms's test results of a single fixture in single-pole wiring configuration for reference purposes; actual results may vary based on field conditions. Dimmer manufacturers may modify their product at any time, without notice to Modern Forms, and therefore Modern Forms cannot ensure future compatibility. For any questions on this report, please contact Modern Forms Customer Service at 1-866-810-6615 or customerservice@modernforms.com.



Dimming Compatibility

ID E1811087V0

Product Family: QUARRY Sku Tested: WS-60028

Related Models

Test Voltage: 120V **Control Type:** ELV

Test Notes: Refer to dimmer manufacturer's dimmer load rating for min and max fixture quantities per dimmer.

Manufacturer	Due deset	Na dal Numban	Test Voltage	Measured	Community				
Manufacturer	Product	Model Number	(V)	Dimming Range Low End	Comments				
Adaptive Phase Dimmers									
Control4	Adaptive	C4-APD120	120	6.0%					
Legrand	Adorne Touch (ELV)	ADTH700RMTUM1	120	79.0%	Flashing at high dimming level				
Legrand	Adorne Touch (TRIAC)	ADTH700RMTUM1	120	86.0%	Not Recommended				
Legrand	Radiant	RH703PTUW	120	10.0%					
Legrand	Adorne (ELV)	ADTP703TUW4	120	7.0%					
Legrand	Adorne (TRIAC)	ADTP703TUW4	120	6.0%	Not Recommended				
Cooper	AL Series	AAL06	120	94.0%	Flicker at high dimming level				
Reverse Phase Dimmers (ELV)									
Lutron	Nova T	NTELV-600	120	7.0%					
Lutron	Diva	DVELV-300P	120	6.0%					
Lutron	Maestro	MAELV-600	120	6.0%					
Lutron	Skylark	SELV-300P	120	7.0%					
Leviton	Illumatech	IPE04-1LZ	120	11.0%					
Lutron	Maestro	RRD-6NA	120	6.0%					
Leviton	SureSlide	6615-P0W	120	9.0%					
Leviton	Decora	DSE06-10Z	120	7.0%					
Lutron	Caseta	PD-5NE	120	11.0%	Flicker below 11%				
Lutron	Homeworks	HRD-5NE	120	N/A	Flashing at high dimming level				
Lutron	Homeworks	HQRD-6NA	120	7.0%					
Leviton	Renoir II	AWSMT-EBW	120	7.0%					
Lutron	Grafik-Eye	GRX-3103-A-G	120	11.0%	Flicker below 11%				
Forward Phase Dimmers (TRIAC)									
Lutron	Maestro	MACL-153M-WH	120	41.0%	Not Recommended				
Lutron	Diva	DVCL-153P	120	41.0%	Not Recommended				
Legrand	Adorne Paddle	ADPD453LW2	120	N/A	Not Recommended				
Lutron	Ariadni	AYCL-153PH	120	38.0%	Not Recommended				
Lutron	Skylark	SCL-153P-WH	120	44.0%	Not Recommended				
Lutron	Maestro	MA-600-WH	120	N/A	Not Recommended				
Leviton	SureSlide	6674-POW	120	50.0%	Not Recommended				
Lutron	Caseta	PD-6WCL	120	37.0%	Not Recommended				
Legrand	Harmony	HCL453PW	120	34.0%	Not Recommended				
Legrand	Radiant	RHCL453PW	120	79.0%	Not Recommended				

Perceived light level percentage is the square root of the measured light level percentage, per IESNA Lighting Handbook. This report reflects Modern Forms's test results of a single fixture in single-pole wiring configuration for reference purposes; actual results may vary based on field conditions. Dimmer manufacturers may modify their product at any time, without notice to Modern Forms, and therefore Modern Forms cannot ensure future compatibility. For any questions on this report, please contact Modern Forms Customer Service at 1-866-810-6615 or customerservice@modernforms.com.



Dimming Compatibility

ID E1811087V0

Product Family: QUARRY Sku Tested: WS-60038

Related Models

Test Voltage: 120V **Control Type:** ELV

Test Notes: Refer to dimmer manufacturer's dimmer load rating for min and max fixture quantities per dimmer.

D.C. and S. adams of	Due deset	No del Number	Test Voltage	Measured	Commont.					
Manufacturer	Product	Model Number	(V)	Dimming Range Low End	Comments					
	Adaptive Phase Dimmers									
Control4	Adaptive	C4-APD120	120	6.0%						
Legrand	Adorne Touch (ELV)	ADTH700RMTUM1	120	79.0%	Flashing at high dimming level					
Legrand	Adorne Touch (TRIAC)	ADTH700RMTUM1	120	86.0%	Not Recommended					
Legrand	Radiant	RH703PTUW	120	10.0%						
Legrand	Adorne (ELV)	ADTP703TUW4	120	7.0%						
Legrand	Adorne (TRIAC)	ADTP703TUW4	120	6.0%	Not Recommended					
Cooper	AL Series	AAL06	120	94.0%	Flicker at high dimming level					
Reverse Phase Dimmers (ELV)										
Lutron	Nova T	NTELV-600	120	7.0%						
Lutron	Diva	DVELV-300P	120	6.0%						
Lutron	Maestro	MAELV-600	120	6.0%						
Lutron	Skylark	SELV-300P	120	7.0%						
Leviton	Illumatech	IPE04-1LZ	120	11.0%						
Lutron	Maestro	RRD-6NA	120	6.0%						
Leviton	SureSlide	6615-P0W	120	9.0%						
Leviton	Decora	DSE06-10Z	120	7.0%						
Lutron	Caseta	PD-5NE	120	11.0%	Flicker below 11%					
Lutron	Homeworks	HRD-5NE	120	N/A	Flashing at high dimming level					
Lutron	Homeworks	HQRD-6NA	120	7.0%						
Leviton	Renoir II	AWSMT-EBW	120	7.0%						
Lutron	Grafik-Eye	GRX-3103-A-G	120	11.0%	Flicker below 11%					
Forward Phase Dimmers (TRIAC)										
Lutron	Maestro	MACL-153M-WH	120	41.0%	Not Recommended					
Lutron	Diva	DVCL-153P	120	41.0%	Not Recommended					
Legrand	Adorne Paddle	ADPD453LW2	120	N/A	Not Recommended					
Lutron	Ariadni	AYCL-153PH	120	38.0%	Not Recommended					
Lutron	Skylark	SCL-153P-WH	120	44.0%	Not Recommended					
Lutron	Maestro	MA-600-WH	120	N/A	Not Recommended					
Leviton	SureSlide	6674-POW	120	50.0%	Not Recommended					
Lutron	Caseta	PD-6WCL	120	37.0%	Not Recommended					
Legrand	Harmony	HCL453PW	120	34.0%	Not Recommended					
Legrand	Radiant	RHCL453PW	120	79.0%	Not Recommended					

Perceived light level percentage is the square root of the measured light level percentage, per IESNA Lighting Handbook. This report reflects Modern Forms's test results of a single fixture in single-pole wiring configuration for reference purposes; actual results may vary based on field conditions. Dimmer manufacturers may modify their product at any time, without notice to Modern Forms, and therefore Modern Forms cannot ensure future compatibility. For any questions on this report, please contact Modern Forms Customer Service at 1-866-810-6615 or customerservice@modernforms.com.