

Dimming Compatibility

ID E2210006V0

Product Family:

Sku Tested: WS-82310

Related Models

Test Voltage: 120-277V

Control Type: ELV,TRIAC,MLV,0-10V

Test Notes: Refer to dimmer manufacturer's dimmer load rating for min and max fixture quantities per dimmer.

Manufacturer	Product	Model Number	Test Voltage (V)	Measured Dimming Range Low End	Comments
Adaptive Phase Dimmers					
Control4	Adaptive	C4-APD120	120	25.0%	Flicker below 25%
Legrand	Adorne Touch (ELV)	ADTH700RMTUM1	120	75.0%	Flicker at high dimming level; Turn on time >0.5s at the lowest dimming level
Legrand	Adorne Touch (TRIAC)	ADTH700RMTUM1	120	0.9%	Not Recommended
Legrand	Radiant	RH703PTUW	120	2.0%	
Legrand	Adorne (ELV)	ADTP703TUW4	120	25.0%	Flicker below 25%
Legrand	Adorne (TRIAC)	ADTP703TUW4	120	2.0%	Not Recommended
Cooper	AL Series	AAL06	120	2.0%	
Control4	Adaptive	C4-APD277	277	0.8%	
Forward Phase Dimmers (TRIAC)					
Lutron	Maestro	MACL-153M-WH	120	5.0%	
Lutron	Diva	DVCL-153P	120	0.7%	Turn on time >0.5s at the lowest dimming level
Legrand	Adorne Paddle	ADPD453LW2	120	86.0%	Flashing at high dimming level
Lutron	Ariadni	AYCL-153PH	120	4.0%	Turn on time >0.5s at the lowest dimming level
Lutron	Skylark	SCL-153P-WH	120	0.9%	Turn on time >0.5s at the lowest dimming level
Lutron	Maestro	MA-600-WH	120	N/A	Dimmer not responsive
Leviton	SureSlide	6674-POW	120	4.0%	
Lutron	Caseta	PD-6WCL	120	0.4%	
Legrand	Harmony	HCL453PW	120	N/A	Flashing at all dimming levels
Legrand	Radiant	RHCL453PW	120	N/A	Flashing at all dimming levels
0-10V Dimmers					
Lutron	Nova T	NTSTV	120	9.0%	
Leviton	Decora	IP710-LFZ	120	3.0%	
Control4	Adaptive	C4-TV120277	120	3.0%	
Lutron	Diva	DVSTV	120	3.0%	
Leviton	Renoir	AWSMT-7DW	120	17.0%	
Legrand	Radiant	RH4FBL3PW	120	3.0%	
Lutron	Nova T	NTSTV	277	10.0%	
Leviton	Decora	IP710-LFZ	277	2.0%	Flicker below 2%
Control4	Adaptive	C4-TV120277	277	3.0%	Flicker below 3%
Lutron	Diva	DVSTV	277	3.0%	Flicker below 3%
Legrand	Radiant	RH4FBL3PW	277	2.0%	Flicker below 2%

Perceived light level percentage is the square root of the measured light level percentage, per IESNA Lighting Handbook. This report reflects Modern Forms's test results of a single fixture in single-pole wiring configuration for reference purposes; actual results may vary based on field conditions. Dimmer manufacturers may modify their product at any time, without notice to Modern Forms, and therefore Modern Forms cannot ensure future compatibility. For any questions on this report, please contact Modern Forms Customer Service at 1-866-810-6615 or customerservice@modernforms.com.