INSTALLATION INSTRUCTIONS

599-LED Flush Mount

FM-59922/FM-59933

MODERN FORMS

CAUTION: To prevent electrical shock, ensure electricity has been turned off at the circuit breaker before beginning.

- Read all instructions before installing.
- System is intended for installation by a licensed electrician in accordance with the National Electrical Code (NEC) and local regulations.
- When handling the fixture, do not apply pressure to the LEDs. Hold the fixture by the base only.
- Retain installation instructions for future maintenance reference.

WARNING: All parts must be used as indicated in these instructions. This product is designed for use only with the supplied parts and/or accessories designated for use by Modern Forms. Substitution of parts or accessories not designated for use with this product by Modern Forms could result in personal injury or property damage, and will void the warranty. Contact an authorized dealer or the manufacturer if any parts are damaged or missing.

MAINTENANCE NOTE: Coastal conditions may cause mineral and residue build-up on the fixture. We recommend that customers in coastal areas clean all external surfaces of the fixture once every two weeks with a wet cloth.

MISE EN GARDE: Pour éviter tout choc électrique, assurez-vous que le disjoncteur soit mis hors tension avant de commencer.

- Lisez toutes les instructions avant l'installation.
- Le système doit être installé par un électricien licensié conformément au code national de l'électricité (NEC), et également aux règlements locaux.
- Lors de la manipulation du luminaire, n'appuyez pas sur les LED. Tenez-le uniquement par la base.

ATTENTION: Toutes les pièces doivent être utilisées comme indiqué dans ces instructions. Ce produit est conçu pour être utilisé seulement avec les pièces et/ou accessoires fournis pour être utilisés avec les produits Modern Forms. Remplacer des pièces ou accessoires non conçus pour ce produit Modern Forms pourrait causer des dommages corporels ou matériels et pourrait également causer l'annulation de la garantie. Veuillez contacter un revendeur autorisé ou le fabricant si des pièces manquent ou sont endommagées.

NOTE D'ENTRETIEN: Les conditions côtières peut causer une accumulation de minéraux et de résidue sur le luminaire. Nous recommendons aux clients qui resident dans les zones côtières de nettoyer toutes les surfaces externes du luminaire une fois toutes les deux semaines avec un chiffon humide.

HARDWARE





Wire Connector Qty: 3pcs+1 Extra





Mounting Screw Qty:1 Extra





Wood Screw Qty: 4pcs+1 Extra





Plastic Anchor Qty: 4pcs+1 Extra

INSTALLATION INSTRUCTIONS

599-LED Flush Mount

FM-59922/FM-59933

MODERN FORMS

PREPARATION

- 1. Shut off the power at the circuit breaker and remove existing fixture, including the crossbar.
- Carefully unpack your new fixture and lay out all the parts on a clear area. Be careful not to lose any small parts necessary for installation.

MOUNTING THE FIXTURE (Fig. 1)

- Remove the mounting screw (B) and back plate from the fixture.
- Drill holes in the wall aligned with the key holes located in the mounting back plate, insert the plastic anchor (D).
- Secure mounting back plate to the junction box using junction box screws, fasten it to the wall using wood screw (C).
- Secure the mounting back plate to the junction box using standard junction box screws that comes with the junction box.

Note: (i) using any other non-original-manufacturer provided junction box screw may result in safty issue;

(ii) The side of the mounting plate marked "GND" must face out.

A Wire Connector Junction Box Bare Copper Ground Wire White Wire D Plastic Anchor Black Wire Safety Cords Mounting back Plate (Only FM-59933) Wood Screw Junction Box Screw B Mounting Screw Driver(Canopy Inside) Lamp Body 4"L*4"W*5/8"H Safety Cords Petal Shade

CONNECTING THE WIRES (Fig. 2)

7. Connect the driver's input wires to junction box wires as shown in Fig. 2, making sure that all wire connectors (A) are secured. If your outlet box has a green or bare copper ground wire, connect the fixture's ground wire to it. Otherwise, connect the fixture's ground wire directly to the back plate using the screw provided. After wires are connected, tuck them carefully inside the junction box.

FIG. 1

8. Properly secure the safety cord to the bracket on mounting back plate to temporary hang the fixture in place.

COMPLETING THE INSTALLATION

- Secure the fixture to the mounting back plate using the mounting screw (B).
- 10. Hook the safety cords to the lamp body, attach the petal shade on the lamp body using internal magnet.

DIMMING WIRING INFORMATION (Fig. 3)

- 11. This fixture features electronic low voltage (ELV or TRAIC) or 0-10V dimming capabilities. See notes below for specific dimming wires information.
- 12. To utilize ELV or TRAIC dimming: use wires black (hot), white (neutral) and bare copper ground wire (ground).
- 13. To utilize 0-10V dimming: use wire purple (dim+), pink or gray (dim-), black (hot), white (neutral) and bare copper ground wire (ground).

NOTE: Make sure to connect 0-10V prior to power-up the fixture in order to allow the 0-10V dimming to function properly.




FIG. 2 Wiring



Fixture Wires	House Wires
Black or	Black
Smooth	(Hot)
Fixture Wires	House Wires
White or	White

Fixture Wires Bare wire (Ground)


Ribbed

House Wires Green or Bare Copper (Ground)

(Neutral)

FM-59922 Back Plate





FM-59933 Back Plate

modernforms.com Phone (800) 526.2588 (800) 526.2585

Headquarters/Eastern Distribution Center 44 Harbor Park Drive Port Washington, NY 11050

Central Distribution Center 1600 Distribution Ct Lithia Springs, GA 30122

Western Distribution Center 1750 Archibald Avenue Ontario, CA 91760

