

DDERN FORMS



Transitional style meets smart technology with this versatile smart fan available in four weather-resistant finishes as well as a 316 marine-grade stainless steel for harsh outdoor climates. The 42" style is ideal for patios and breakfast nooks, while the 52" and 60" versions are perfect for living rooms and large bedrooms. The LED luminaire, powered by WAC, takes this design from beautiful to brilliant. Connect with our exclusive Modern Forms app for even more life enhancements.

FEATURES

- 6 fan speeds through both Summer and Winter Modes
- · Silent DC motor
- Includes BT remote control

PRODUCT DESCRIPTION

- Optional wall control for 3, 4-way control sold separately
- · Compatible with Modern Forms app

AIRFLOW/ENERGY EFFICIENCY

Weighted-Average/High Airflow CFM: 3199/4981(High) Weighted-Average/High Energy Use (W): 13/25 (High)

Estimated Yearly Energy Cost (\$):

Weighted-Average/High Efficiency (CFM/W): 211/192 (High)

Max RPM: 199

ORDER NUMBER

Model	Hous	ing	Blade	Blade				
FR-W1801-42L	BZ	Bronze	BZ	Bronze				
	GH	Graphite	WG	Weathered Gray				
	MB	Matte Black	MB	Matte Black				
	MW	Matte White	MW	Matte White				
	SS	Stainless Steel	SS	Stainless Steel				

6" 11¼"14" 9" 42"

SPECIFICATIONS

Total Power:

Construction: Aluminum, ABS Blade: 13° Pitch, 42" sweep .75"W. x 4.5"H included Downrod:

Mounting Slope: Up to 30° 80" **Hanging Weight:** 15.5 lbs

Standards: UL/cUL Wet Location listed, Title 24 JA8-2016

Compliant, Title 20, Energy Star rated

125 x 20 sensorless DC motor **Motor Type:**

44.5W

WIRELESS PERFORMANCE

Wi-Fi Range: Up to 150 ft* **Bluetooth Range:** Up to 150 ft

LUMINAIRE PERFORMANCE

Light Source: I FD **Light Wattage:** 19.5W Lumens/Delivered Lumens: 1600/846 Dimming: Integrated CRI:

Color Temperature: 3000K (2700K/3500K options available)

Rated Life: 50,000 hours

Example: FR-W1801-42L-MW

For 2700K add "-27"; for 3500K add "-35" before the finish: FR-W1801-42L-27-MW

*Results may vary based on application and surroundings.

*This fan comes uni-pack - blade select options are not available



The Modern Forms app synchronizes seamlessly with smart home devices you already own













modernforms.com Phone (800) 526.2588 (800) 526.2585

Headquarters/Eastern Distribution Center Central Distribution Center 44 Harbor Park Drive Port Washington, NY 11050

1600 Distribution Ct Lithia Springs, GA 30122 Western Distribution Center 1750 Archibald Avenue Ontario, CA 91760





OPTIONAL ACCESSORIES

OPTIONAL ACCESSORIES			
Bluetooth Wall Control	F-WCBT	WT White	Control fan speed and light brightness, and switch between Summer and Winter Modes. Additional Wall Controls can be purchased separately for multiple location control.
Bluetooth Remote Control	F-RCBT	WT White	Control fan speed and light brightness, and switch between Summer and Winter Modes. Compatible with Modern Forms Smart Fans. Includes easy-to-install wall cradle and batteries.
Downrod	XF-12 12IN XF-18 18IN XF-24 24IN XF-36 36IN XF-48 48IN XF-60 60IN XF-72 72IN		All our downrods are .75 (in) and are threaded on the motor end to create an extra layer of security and allow for adjustments in the field.
Downrod Couplers	XF-I		Connects two downrods together.
Sloped Ceiling Kit	XF-SCK		Designed to accommodate buildings with steeper sloped ceilings up to 45° or 12/12 pitch.

Examples: Wall Control: F-WCBT-WT, Remote Control: F-RCBT-WT, Downrod: XF-12-BN, Downrod Coupler: XF-I-MB, Sloped Ceiling Kit: XF-SCK-MW

SUGGESTED DOWNROD HEIGHT USAGE

Ceiling Height	15'	14'	13'	12'	11'	10'	9'
Downrod	72"	60"	48"	36"	24"	18"	12"

SLOPED CEILING DEGREE CONVERSION CHART

Degree	4-8°	9-13°	14-17°	18-21°	22-25°	26-29°	30-32°	33-35°	36-38°	39-41°	42-44°	45°
Ceiling Slope	1/12	2/12	3/12	4/12	5/12	6/12	7/12	8/12	9/12	10/12	11/12	12/12
Pitch	pitch	pitch	pitch	pitch	pitch	pitch	pitch	pitch	pitch	pitch	pitch	pitch

Supplied mounting brackets allow mounting on ceiling slopes up to 30° (7/12 pitch). Optional slope kit allows mounting on ceilings up to 45° (12/12 pitch). The receiver will mount inside canopy up to 45° .

NOTE: Recommended maximum downrod length of 72" with 80" lead wire