


HYDRA

FR-W1805-120L

120" Ceiling Fan

MODERN FORMS

SMART FANS



PRODUCT DESCRIPTION

As its name suggests, Hydra is all about water. Like all of our smart fans, it's wet-rated for outdoor use so you can maintain the continuity of your décor inside and out. Even with an impressive 120" blade sweep, this epically scaled smart fan moves a massive amount of air without consuming much energy, thanks to a powerful DC motor that runs up to 70% more efficient than AC motors. Control it all with our exclusive Modern Forms app. Available in 80 inches, 96 inches and 120 inches.

FEATURES

- 6 fan speeds through both Summer and Winter Modes
- Silent DC motor
- Includes BT wall control
- Optional wall control for 3, 4-way control sold separately
- Compatible with Modern Forms app

AIRFLOW/ENERGY EFFICIENCY

Weighted-Average/High Airflow CFM	2798/13300
Weighted-Average/High Energy Use (W):	13/44
Estimated Yearly Energy Cost (\$):	4
Weighted-Average/High Efficiency (CFM/W)	211/302
Max RPM:	40

ORDER NUMBER

Model	Housing	Blade
FR-W1805-120L	BZ Bronze	BZ Bronze
	TT Titanium Silver	TT Titanium Silver
	MB Matte Black	MB Matte Black
	MW Matte White	MW Matte White

Example: **FR-W1805-120L-MB**

For 2700K add "-27" ; for 3500K add "-35" before the finish: **FR-W1805-120L-27-MW**

***Results may vary based on application and surroundings.**

***This fan comes uni-pack - blade select options are not available**

The Modern Forms app synchronizes seamlessly with smart home devices you already own



SPECIFICATIONS

Construction:	Aluminum, ABS
Blade:	14° Pitch, 120" sweep
Downrod:	.75"W x 4.5"H included
Mounting Slope:	Up to 30°
Wire:	80"
Hanging Weight:	46 lbs
Total Power:	67.5W
Standards:	ETL/cETL Wet Location listed, Title 24 JA8-2016 Compliant, Title 20, Energy Star rated
Motor Type:	168 x 30 sensorless DC motor

WIRELESS PERFORMANCE

Wi-Fi Range:	Up to 150 ft*
Bluetooth Range:	Up to 150 ft*

LUMINAIRE PERFORMANCE

Light Source:	LED
Light Wattage:	23.5W
Lumens/Delivered Lumens:	2100/1031
Dimming:	Integrated
CRI:	90
Color Temperature:	3000K (2700K/3500K options available)
Rated Life:	50,000 hours

modernforms.com
Phone (800) 526.2588
Fax (800) 526.2585

Headquarters/Eastern Distribution Center
44 Harbor Park Drive
Port Washington, NY 11050

Central Distribution Center
1600 Distribution Ct
Lithia Springs, GA 30122





Western Distribution Center
1750 Archibald Avenue
Ontario, CA 91760

HYDRA

FR-W1805-120L
120" Ceiling Fan

MODERN FORMS SMART FANS

OPTIONAL ACCESSORIES

<p>Bluetooth Wall Control</p> 	<p>F-WCBT</p>	<p>WT White</p>	<p>Control fan speed and light brightness, and switch between Summer and Winter Modes. Additional Wall Controls can be purchased separately for multiple location control.</p>
<p>Bluetooth Remote Control</p> 	<p>F-RCBT</p>	<p>WT White</p>	<p>Control fan speed and light brightness, and switch between Summer and Winter Modes. Compatible with Modern Forms Smart Fans. Includes easy-to-install wall cradle and batteries.</p>
<p>Downrod</p> 	<p>XF-12 12IN XF-18 18IN XF-24 24IN XF-36 36IN XF-48 48IN XF-60 60IN XF-72 72IN</p>		<p>All our downrods are .75 (in) and are threaded on the motor end to create an extra layer of security and allow for adjustments in the field.</p>
<p>Downrod Couplers</p> 	<p>XF-I</p>		<p>Connects two downrods together.</p>
<p>Sloped Ceiling Kit</p> 	<p>XF-SCK</p>		<p>Designed to accommodate buildings with steeper sloped ceilings up to 45° or 12/12 pitch.</p>

Examples: Wall Control: **F-WCBT-WT**, Remote Control: **F-RCBT-WT**, Downrod: **XF-12-BN**, Downrod Coupler: **XF-I-MB**, Sloped Ceiling Kit: **XF-SCK-MW**

SUGGESTED DOWNROD HEIGHT USAGE

Ceiling Height	15'	14'	13'	12'	11'	10'	9'
Downrod	72"	60"	48"	36"	24"	18"	12"

SLOPED CEILING DEGREE CONVERSION CHART

Degree	4-8°	9-13°	14-17°	18-21°	22-25°	26-29°	30-32°	33-35°	36-38°	39-41°	42-44°	45°
Ceiling Slope	1/12	2/12	3/12	4/12	5/12	6/12	7/12	8/12	9/12	10/12	11/12	12/12
Pitch	pitch	pitch	pitch	pitch	pitch	pitch	pitch	pitch	pitch	pitch	pitch	pitch

Supplied mounting brackets allow mounting on ceiling slopes up to 30° (7/12 pitch). Optional slope kit allows mounting on ceilings up to 45° (12/12 pitch). The receiver will mount inside canopy up to 45°.

NOTE: Recommended maximum downrod length of 72" with 80" lead wire