
## ROBOTO

FR-W1910-62

62" Ceiling Fan







### **PRODUCT DESCRIPTION**

Like all our smart fans, Roboto is Wet Rated to be perfect for indoor and outdoor applications. Two size options are available to complete any deck, pergola, room or living space. The quiet DC motor is 70% more efficient than AC motors, and our free Modern Forms app lets you control fan speed, set schedules, and integrate with smart home devices.

#### **FEATURES**

- · 6 fan speeds through both Summer and Winter Modes
- · Silent DC motor
- Includes BT remote control
- Optional wall control sold separately
- Compatible with Modern Forms app

#### AIRFLOW/ENERGY EFFICIENCY

Weighted-Average/High Airflow CFM: 5612/7757 Weighted-Average/High Energy Use (W): 13/34 **Estimated Yearly Energy Cost (\$):** 4 Weighted-Average/High Efficiency (CFM/W): 211/188 Max RPM: 140

## **ORDER NUMBER**

Model	Hous	ing	Blade			
FR-W1910-62	BA	Brushed Aluminum	TT	Titanium		
	MB	Matte Black	MB	Matte Black		
	MW	Matte White	MW	Matte White		
	OB	Oil Rubbed Bronze	BZ	Bronze		

Example: FR-W1910-62-MB

# **SPECIFICATIONS**

**Construction:** Aluminum, ABS Blade: 14° Pitch, 52"sweep .75"W x 6"H included Downrod:

**Mounting Slope:** Up to 30° 80" **Hanging Weight:** 13 lbs **Total Power:** 34W

Standards: UL/cUL Wet Location listed, Title 24 JA8-2016

Compliant, Title 20, Energy Star rated

125 x 20 sensorless DC motor **Motor Type:** 

### **WIRELESS PERFORMANCE**

Wi-Fi Range: Up to 150 ft\* **Bluetooth Range:** Up to 150 ft\*

\*Results may vary based on application and surroundings. \*This fan comes uni-pack - blade select options are not available



The Modern Forms app synchronizes seamlessly with smart home devices you already own













modernforms.com Phone (800) 526.2588 (800) 526.2585

Headquarters/Eastern Distribution Center Central Distribution Center 44 Harbor Park Drive Port Washington, NY 11050

1600 Distribution Ct Lithia Springs, GA 30122 Western Distribution Center 1750 Archibald Avenue Ontario, CA 91760

62" Ceiling Fan



### **OPTIONAL ACCESSORIES**

Bluetooth Wall Control	F-WCBT	<b>WT</b> White	Control fan speed and light brightness, and switch between Summer and Winter Modes. Additional Wall Controls can be purchased separately for multiple location control.
Bluetooth Remote Control	F-RCBT	<b>WT</b> White	Control fan speed and light brightness, and switch between Summer and Winter Modes. Compatible with Modern Forms Smart Fans. Includes easy-to-install wall cradle and batteries.
Downrod	XF-12 12IN XF-18 18IN XF-24 24IN XF-36 36IN XF-48 48IN XF-60 60IN XF-72 72IN		All our downrods are .75 (in) and are threaded on the motor end to create an extra layer of security and allow for adjustments in the field.
Downrod Couplers	XF-I		Connects two downrods together.
Sloped Ceiling Kit	XF-SCK		Designed to accommodate buildings with steeper sloped ceilings up to 45° or 12/12 pitch.

Examples: Wall Control: F-WCBT-WT, Remote Control: F-RCBT-WT, Downrod: XF-12-BN, Downrod Coupler: XF-I-MB, Sloped Ceiling Kit: XF-SCK-MW

### SUGGESTED DOWNROD HEIGHT USAGE

Ceiling Height	15'	14'	13'	12'	11'	10'	9'
Downrod	72"	60"	48"	36"	24"	18"	12"

### **SLOPED CEILING DEGREE CONVERSION CHART**

Degree	4-8°	9-13°	14-17°	18-21°	22-25°	26-29°	30-32°	33-35°	36-38°	39-41°	42-44°	45°
Ceiling Slope	1/12	2/12	3/12	4/12	5/12	6/12	7/12	8/12	9/12	10/12	11/12	12/12
Pitch	pitch	pitch	pitch	pitch	pitch	pitch	pitch	pitch	pitch	pitch	pitch	pitch

Supplied mounting brackets allow mounting on ceiling slopes up to  $30^{\circ}$  (7/12 pitch). Optional slope kit allows mounting on ceilings up to  $45^{\circ}$  (12/12 pitch). The receiver will mount inside canopy up to  $45^{\circ}$ .

NOTE: Recommended maximum downrod length of 72" with 80" lead wire